

# The **fouridx** package\*

Stefan Karrmann  
s.karrmann at web.de

File Date 2008/03/27, Printed November 21, 2013

## **Abstract**

This package enables left subscripts and superscripts in math mode. These subscripts and superscripts are automatically raised for better fitting to the symbol they belong to. This is done in such a way that the left and right subscripts and superscripts are set on the same line, respectively.

## **Contents**

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Old bugs/regression . . . . .	2
1.2	Comparison with sideset . . . . .	2
<b>2</b>	<b>Usage of the package</b>	<b>2</b>
<b>3</b>	<b>The implementation</b>	<b>3</b>

## **Copyright**

Copyright 2007, 2013 Stefan Karrmann.

This program can be redistributed and/or modified under the terms of the LaTeX Project Public License Distributed from CTAN archives in directory macros/latex/base/lppl.txt; either version 1 of the License, or any later version.

## **1 Introduction**

In mathematical equations, it is sometimes necessary to use indices (subscript or superscript) that are positioned at the left side of a symbol. In tensor mathematics, for instance, some notations use a transposed sign at the left side of the symbol:

$${}^t(A_{ij}) = (A_{ji})$$

---

\*This file has version 1.00 last revised 2008/03/27.

For symbols with a normal character height, this can be reached by simply put the indices without an own symbol:

`$_1^2a_3^4$`

$\overset{2}{1} \overset{4}{a_3}$

Is the symbol larger, this leads to unsatisfactory results:

`$_{^1_2}\left(\frac{1}{b}\right)^3_4$`

$\overset{3}{\underset{4}{\left(\frac{1}{b}\right)}}$

If the subscripts on the left and right side are of different height or the left subscripts and superscripts are of different width, the result is also unsatisfactory:

`$_{^{(k)}_n}A^x_{\overline{x}\mid}$`

$\overset{(k)}{n} A^x_{\overline{x}\mid}$

A better output can be reached by using the package `fouridx.sty`:

`\fourIdx{1}{2}{3}{4}{\left(\frac{1}{b}\right)}`

$\overset{3}{\underset{4}{\left(\frac{1}{b}\right)}}$

`\fourIdx{(k)}{n}{x}{\overline{x}\mid}A`

$\overset{(k)}{n} A^x_{\overline{x}\mid}$

## 1.1 Old bugs/regression

Error	version	old	actual
math style ignored	1.00	$\overset{1}{2} \overset{3}{5_4}$	$\overset{1}{2} \overset{3}{5_4}$
hang over at left after line breaks	1.00	$\mid \text{Start of line}$ $\overset{1}{2} \overset{3}{5_4}$	$\mid \text{Start of line}$ $\overset{1}{2} \overset{3}{5_4}$
wrong positions if nested	1.00	$\mid^2 \overset{1}{5} \overset{3}{1} \overset{3}{2} \overset{3}{2} \overset{3}{4}_4$	$\mid^2 \overset{1}{5} \overset{3}{1} \overset{3}{2} \overset{3}{2} \overset{3}{4}_4 \mid$

## 1.2 Comparison with sideset

The command `sideset` from the `amsmath` package has similiar functionality. It requires that the central box is a math operator an it typesets the left super- and subscript left aligned while `fourIdx` uses right alignment. Which suits better depends on the purpose.

## 2 Usage of the package

One command is provided by the package.

`\fourIdx` The `\fourIdx` command has the syntax `\fourIdx{\langle left superscript\rangle}{\langle left subscript\rangle}{\langle right superscript\rangle}{\langle right subscript\rangle}{\langle symbol\rangle}`. This command typesets the symbol `\langle symbol\rangle` with indices on the left and on the right side. Example:

$$\$\\fourIdx{1}{2}{3}{4}{\left(\\frac{1}{b}\\right)^3} \\quad 2\\left(\\frac{1}{b}\\right)_4^3$$

You may omit left or right indices by using empty arguments.

The next example shows the same in the different mathematical styles:

$$2\\left(\\frac{1}{b}\\right)_4^3 \\quad 2\\left(\\frac{1}{b}\\right)_4^3 \\quad 2\\left(\\frac{1}{b}\\right)_4^3 \\quad 2\\left(\\frac{1}{b}\\right)_4^3$$

### 3 The implementation

Heading of the package:

```
1 \\NeedsTeXFormat{LaTeX2e}[1995/12/01]
2 \\ProvidesPackage{fouridx}[\filedate\space v\fileversion\space Four indices]
```

`\fourIdx` Command for left and right indices.

```
3 \\newcommand{\\fourIdx}[5]{%
4   \\ensuremath{\\mathchoice{%
5     {\\setbox1=\\hbox{$\\scriptstyle{#1}$}%
6     \\setbox2=\\hbox{$\\scriptstyle{#2}$}%
7     \\setbox5=\\hbox{$\\displaystyle{#5}$}%
8     \\hspace*{\\ifnum\\wd1>\\wd2\\wd1\\else\\wd2\\fi}%
9     \\copy5^{\\scriptstyle\\hspace{-\\wd1}\\hspace{-\\wd5}#1\\hspace{\\wd5}#3}%
10    _{\\scriptstyle\\hspace{-\\wd2}\\hspace{-\\wd5}#2\\hspace{\\wd5}#4}%
11  }{%
12    {\\setbox1=\\hbox{$\\scriptstyle{#1}$}%
13    \\setbox2=\\hbox{$\\scriptstyle{#2}$}%
14    \\setbox5=\\hbox{$\\textstyle{#5}$}%
15    \\hspace*{\\ifnum\\wd1>\\wd2\\wd1\\else\\wd2\\fi}%
16    \\copy5^{\\scriptstyle\\hspace{-\\wd1}\\hspace{-\\wd5}#1\\hspace{\\wd5}#3}%
17    _{\\scriptstyle\\hspace{-\\wd2}\\hspace{-\\wd5}#2\\hspace{\\wd5}#4}%
18  }{%
19    {\\setbox1=\\hbox{$\\scriptscriptstyle{#1}$}%
20    \\setbox2=\\hbox{$\\scriptscriptstyle{#2}$}%
21    \\setbox5=\\hbox{$\\scriptstyle{#5}$}%
22    \\hspace*{\\ifnum\\wd1>\\wd2\\wd1\\else\\wd2\\fi}%
23    \\copy5^{\\scriptscriptstyle\\hspace{-\\wd1}\\hspace{-\\wd5}#1\\hspace{\\wd5}#3}%
24    _{\\scriptscriptstyle\\hspace{-\\wd2}\\hspace{-\\wd5}#2\\hspace{\\wd5}#4}%
25  }{%
26    {\\setbox1=\\hbox{$\\scriptscriptstyle{#1}$}%
27    \\setbox2=\\hbox{$\\scriptscriptstyle{#2}$}%
28    \\setbox5=\\hbox{$\\scriptscriptstyle{#5}$}%
29    \\hspace*{\\ifnum\\wd1>\\wd2\\wd1\\else\\wd2\\fi}%
30    \\copy5^{\\scriptscriptstyle\\hspace{-\\wd1}\\hspace{-\\wd5}#1\\hspace{\\wd5}#3}%
31    _{\\scriptscriptstyle\\hspace{-\\wd2}\\hspace{-\\wd5}#2\\hspace{\\wd5}#4}%
32  }{%
33 }}
```